

Walco

ALLSPREAD 12.75 PTO

3 POINT LINKAGE



DELMADÉ

PTY LTD

Shaping the Land

Helping farmers boost
production!



FEATURES & BENEFITS

- Hopper & guards are UV & corrosion resistant polyethylene *for longer service*
- Frame is strong steel construction which is hot-dip galvanised *for durability*
- Aperture shutter is stainless steel *for no maintenance*
- Aperture has twin drop points *for even spreading & even growth*
- Spinner is dished with adjustable fins *for even spreading & even growth*
- Spinner speed 720rpm at 540 pto rpm *for a wide even spread or to save fuel at lower revs*
- Hydraulic open/shut *for ease of operation*

OPTIONAL EXTRAS

- PVC Hopper Cover *for economy*
- Hydraulic Open/Shut
- Quick Hitch

SPECIFICATIONS

- Throw width: 25m at 540 rpm (Urea)
- Working Width: 15m
- Width: 1750mm (1600 inside hopper)
- Height 1185mm

OPTIONAL

Quick Hitch
*for speedy
pick up and
set down*



OPTIONAL

Hydraulic
Open/Shut *for
ease of operation.*



HOPPER CAPACITY

- 1275 Litres
- 1 Tonne bag of Urea

1800 335 623

info@delmade.com.au

7 Roxford Avenue, Westbury, Tasmania

www.delmade.com.au