

Teagle

spir©mix Concrete Mixer



Spir©mix 200H Holds 50 kg of cement and a 6:1 mix of aggregate

EASY LOADING through the wide mouth of the drum.

EASY UNLOADING - the drum rotates in one direction for mixing and in the opposite direction for unloading. Hydraulic motor drive - easily controlled from the tractor seat via the external services spool valve.

GOOD MIX - the deep spirals, needed to give a good unloading action, also give a quick and thorough mix.

GOOD UNLOADING HEIGHT - because the drum does not tip to unload, the discharge height is always good.



	Model 200H
Drum Volume	560 litres (20 cu. ft.)
Approx. Mix Volume	280 litres (10 cu. ft.)
Loading Height to Drum Lip	57cm. (22 in.)
Weight Empty	190 kg. (420 lb.)
Approx. Laden Weight	815 kg. (1790 lb.)
Drum Diameter	82 cm. (32 in.)
Drum Length	111 cm. (43 in.)
Mounting	Cat 2 Linkage
Min. Tractor Size	40 kW (50 HP)

The Company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice

DELMADÉ
PTY LTD
Shaping the Land

1800 335 623
info@delmade.com.au
www.delmade.com.au