



DELMADE TIP TRAILER 2, 4, 6, 8, 10, 12 TONNE MODELS

STRENGTH THAT LASTS A LIFETIME

Specially designed to operate in the harshest of conditions.

The Delmade Farm Tip Trailer is a super heavy-duty monster. Each unit is designed with superb inbuilt strength to easily achieve its tonnage rating. Tasmanian made to suit tough Tasmanian conditions.

DELMADÉ TIP TRAILER 2, 4, 6, 8, 10, 12 TONNE MODELS

Delmade is proud to locally manufacture this seriously durable farm trailer. These units come in four models with from 2 to 12 tonnes. With unlimited uses on the farm and a range of specification options. The Delmade Tip Trailer is an extremely versatile investment offering strength, durability and value-for-money. From rubbish to rocks, fertiliser to fence posts, silage to sheep, timber, hay bales, gravel or machinery, the extra heavy-duty chassis is engineered to perform at full capacity in the toughest of conditions.

FEATURES:

- Removable sides and tailgate – allow versatility and choice of options
- Steel Floor 6mm
- Adjustable H.D. Pole Support (hydraulic option)
- Walking beam tandem axle for difficult terrain
- Tailgate – top mounted pivot hinge
- Tie rails – ensures heaviest loads can be secured
- Swivel tow eyelet – security in difficult conditions
- Large flotation tyres for field conditions
- Light kits and other custom requirements available on request. (Note trailer designed for farm use only)
- Multi-Stage Cylinder – Hydraulic Ram



Rocker Beam Suspension



Swivel tow eyelet



Steel Floor (6 mm)

PRODUCT CODE	RATING	DECK SIZE (MM)	DECK THICKNESS	SIDES	TRANSPORT WIDTH	TOTAL WEIGHT (approx.)	AXLE	TYRES / WHEELS	BRAKES	HYDRAULIC RAM	TIP ANGLE
-	2t	2100(W) x 3100(L)	6mm	400mm	2150mm	850kg	Single	11/15	NO	Single-Stage 1 Cylinder	54°
DTT1404	4t	2200(W) x 3200(L)	6mm	400mm	2250mm	950kg	Single	11.5/80	NO	Single-Stage 1 Cylinder	54°
DTT1400	6t	2400(W) x 3800(L)	6mm	400mm	2450mm	1600kg	Tandem	11.5/80	NO	Multi-Stage 1 Cylinder	54°
DTT1408	8t	2500(W) x 4300(L)	6mm	500mm	2550mm	2100kg	Tandem	400/60	YES	Multi-Stage 2 Cylinder	54°
DTT1410	10t	2500(W) x 4600(L)	6mm	500mm	2550mm	2300kg	Tandem	400/60	YES	Multi-Stage 2 Cylinder	54°
DTT1412	12t	2500(W) x 4800(L)	6mm	500mm	2550mm	3600kg	Tandem	500/50	YES	Multi-Stage 2 Cylinder	54°

DELMADÉ
Shaping the Land

1800 335 623

info@delmade.com.au
www.delmade.com.au